canter level side sealing machines with patented film feed system

Excitement never ends. Star will win you over at first glance. More charm, less consumption. The thrill of an evolution that respects tradition. Progress and emotion, versatility and speed in the first canterlevel side sealing wrapper that works with center folded and flat film. PATENTED AND EXCLUSIVE SYSTEM.

>> general features

Patented system: first machine in the world able to work with center folded and flat film in the same machine. intermittent and box motion: output up to 120 pcs/min film.can work with all kind of film. Film saving & wonderful bag result: tight and beautiful. Canter level structure that allows an easy cleaning and accessibility of the machine, great in the Food Industry as it can work with BARRIER film also in Modified Atmosphere MAP. Stainless steel version available can be combined with a canter level shrink tunnel with opening chamber.

>> specific features

Patented system: first machine in the world able to work with center folder and flat film in the same machine. Available in 2 versions intermittent and box motion: output up to 120 pcs/min film: poliolefine, polypropylene, BOPP, PE, Barrier Film. Film saving: no more than 1 cm waste film tight bag as in a flowpack machine.

And optional: patented saving energy system with siemens-50% of machine consumption saved. Canterlever shrink tunnel with movable and opening shrink tunnel. Canterlever additional in feed belt. Available also in stainless steel version

>> details



Tighter & wonderful bags, perfect for pre Less consumption, less waste, Film economy. printed film.






Film dispenser unit that can work both with Center Folded and Flat film. Patented




Reduced space between the side sealing and the product, to save 10 cm of side film.



Easy change of format: center sealing and triangle-inverting head motorised. Height up 400 mm.



Flexibility: optional side sealing and transversal sealing system for all kind of



Kissing belt mounted as standard in all our machines to pack smaller and round /irregular shape products.



Stainless steel version available



High quality components, ISO certificated.





STAR

side sealing machines

>> technical features

MOD.	500	5001	600	6001
Sealing dimensions	500 mm	500 mm	600 mm	600 mm
Max product width	400 mm	4000 mm	500 mm	500 mm
Max product length	unlimited	unlimited	unlimited	unlimited
Max product height	200 mm	200 mm	200 mm	200 mm
Film width (center Folded & Flat Film sizes)	650 mm	650 mm	750 mm	750 mm
Reel diameter	350 mm	350 mm	350 mm	350 mm
Working height	900+/- 50	900+/- 50	900+/- 50	900+/- 50
Machine weight	800 Kg	800 Kg	800 Kg	800 Kg
Speed	100 p/min - box motion	75 p/min	100 p/min - box motion	75 p/min
Speed - fast version	120 p/min		box motion	



Accessible canter level structure, completely open: perfect for food Industry. Stainless steel version available.